







1 Adapter can only be used with lateral swinging draw hook.
L'adattatore può essere utilizzato solamente con il gancio di trazione laterale oscillante.



- 1 Painted acc. to DCAB AI914. Colour RAL 2004 (Pure Orange).
Verniciatura secondo le istruzioni DCAB AI914, colore RAL 2004 (arancio puro)
- Anti seize grease on all fasteners. Molykote 1000 or equivalent.
Lubrificante anti-grippaggio su tutti gli elementi di fissaggio, Molykote 1000 oppure equivalente.
- Fasteners tightened acc. to DCAB AI907.
Elementi di fissaggio serrati secondo le istruzioni DCAB AI907
- Moving parts greased with Lagermeister 3000+.
Parti mobili lubrificate con Lagermeister 3000+.
- Max draft load: 300kN.
Massimo carico di trazione: 300kN.
- Max buff load: 300kN.
Massimo carico di compressione: 300kN.

MATRICOLA	EMESSO A.T.	EMESSO E
MACCARI	Cappello	Iazzetta
FORNITORE	DELNER	EMISS. UGUAGLIANZE
SIGLA	DISSEGNO DOCUMENTO	FOGLIO
MC1	MC1304908MF01	1/2
COMMESSA	TIPO	MOD
P033		IMOD
DATA	04/11/13	3.04.906
		01

Designed	MEr	Drawn	RoS	Controlled	MEr	Scale	1:2	Weight	30 kg	Compos	1006760	
Adapter Type 10 to UIC Hook							 DELLNER					
Date						2013-09-23		Drawing No.		1045491		
This document is copyright legislation and must not without permission from Dellner Couplers, be given or handed over to any outsider. Trespass give rise to responsibility.											Sheet	1/3

